

Safety Data Sheet

according to WHS Regulations

Printing date 07.06.2019

Revision: 07.06.2019

1 Identification

Product Name: LEATHER PRO-TECH

Other Means of Identification: Mixture

Recommended Use of the Chemical and Restriction on Use: Textile impregnation

Details of Manufacturer or Importer:

Always Dry
 13/48 Hutchinson street
 Burleigh Heads
 Queensland 4226

Phone Number: 1300 761 617

Emergency telephone number: 1300 761 617

2 Hazard(s) Identification

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (7th edition).



flame

Flammable Liquids 2

H225 Highly flammable liquid and vapour.



Serious Eye Damage/Irritation 2A H319 Causes serious eye irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

Signal Word Danger

Hazard Statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 07.06.2019

Revision: 07.06.2019

Product Name: LEATHER PRO-TECH

(Contd. of page 1)

P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use to extinguish: CO ₂ , powder or water spray.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national regulations.

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

CAS: 67-63-0	Propan-2-ol	50 - 60%
	⚠ Flammable Liquids 2, H225; ⚠ Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H336	

4 First Aid Measures

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Do not give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure:

Inhalation: May cause central nervous system depression, dizziness, drowsiness, numbness, headaches, vomiting and narcosis.

Skin Contact: May cause an allergic skin reaction in some people.

Eye Contact: Causes serious eye irritation, redness and swelling.

Ingestion: May be harmful if swallowed.

5 Fire Fighting Measures

Suitable Extinguishing Media:

Alcohol-resistant foam, dry chemical powder or carbon dioxide. Water may be ineffective. Do not use full water jet as it may spread the fire.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon and hydrocarbons.

Highly flammable liquid.

Containers close to fire should be removed if safe to do so. Use water spray to cool fire exposed containers.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 07.06.2019

Revision: 07.06.2019

Product Name: LEATHER PRO-TECH

(Contd. of page 2)

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots. Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material. Do not use combustible absorbents such as sawdust or cellulose. Collect the spilled material and place into a suitable container for disposal. Use only non-sparking tools.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.

Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Protect from heat, sparks, open flames, hot surfaces and direct sunlight. Keep away from strong oxidising agents, strong acids and strong bases.

8 Exposure Controls and Personal Protection

Exposure Standards:

CAS: 67-63-0 Propan-2-ol

NES STEL: 1230 mg/m³, 500 ppm
TWA: 983 mg/m³, 400 ppm

WES STEL: 1230 mg/m³, 500 ppm
TWA: 983 mg/m³, 400 ppm

Engineering Controls:

Maintain air concentration below occupational exposure standards, providing adequate ventilation. Use explosion-proof ventilating equipment.

Respiratory Protection:

Use an approved vapour respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

Protective gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 07.06.2019

Revision: 07.06.2019

Product Name: LEATHER PRO-TECH

(Contd. of page 3)

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form:	Liquid
Colour:	Colourless
Odour:	Solvent-like
Odour Threshold:	No information available
pH-Value:	5 - 10
Melting point/freezing point:	No information available
Initial Boiling Point/Boiling Range:	82 °C
Flash Point:	10 °C
Flammability:	Highly flammable.
Auto-ignition Temperature:	425 °C
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	No information available
Upper:	No information available
Vapour Pressure at 20 °C:	45.79 hPa
Density at 20 °C:	0.78 g/cm ³
Vapour Density:	No information available
Evaporation Rate:	No information available
Solubility in Water:	Completely miscible
Partition Coefficient (n-octanol/water):	No information available
Viscosity:	<10 mPa.s

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.

Chemical Stability: Stable at ambient temperature and under normal conditions of use.

Conditions to Avoid: Heat, sparks, open flames, hot surfaces and direct sunlight.

Incompatible Materials: Strong oxidising agents, strong acids and strong bases.

Hazardous Decomposition Products: Oxides of carbon.

11 Toxicological Information

Toxicity:**LD₅₀/LC₅₀ Values Relevant for Classification:****CAS: 67-63-0 Propan-2-ol**

Oral	LD ₅₀	5,045 mg/kg (rat)
Dermal	LD ₅₀	12,800 mg/kg (rabbit)
Inhalation	LC ₅₀ /4 h	30 mg/l (rat)

Acute Health Effects**Inhalation:**

May cause central nervous system depression, dizziness, drowsiness, numbness, headaches, vomiting and narcosis.

Skin: May cause an allergic skin reaction in some people.

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 07.06.2019

Revision: 07.06.2019

Product Name: LEATHER PRO-TECH

(Contd. of page 4)

Eye: Causes serious eye irritation, redness and swelling.**Ingestion:** May be harmful if swallowed.**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.**Serious Eye Damage / Irritation:** Causes serious eye irritation.**Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Isopropyl alcohol is classified by IARC as Group 3 - Not classifiable as to its carcinogenicity to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:** May cause drowsiness and dizziness.**Specific Target Organ Toxicity (STOT) - Repeated Exposure:**

Based on classification principles, the classification criteria are not met.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** No information available**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available

12 Ecological Information

Ecotoxicity:**Aquatic toxicity:****CAS: 67-63-0 Propan-2-ol**

EC ₅₀ /48 h	100 mg/l (daphnia)
EC ₅₀ /72 h	100 mg/l (scenedesmus subspicatus)
LC ₅₀ /96 h	1,400 mg/l (bluegill)
	9,640 mg/l (fathead minnow)
LC ₅₀ /48 h	8,970 mg/l (golden orfe)

Persistence and Degradability: No further relevant information available.**Bioaccumulative Potential:** No further relevant information available.**Mobility in Soil:** No further relevant information available.**Other adverse effects:** No further relevant information available.

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.**Special Precautions for Landfill or Incineration:**

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number**ADG, IMDG, IATA**

UN1219

Proper Shipping Name**ADG, IMDG, IATA**

ISOPROPANOL (ISOPROPYL ALCOHOL) mixture

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 07.06.2019

Revision: 07.06.2019

Product Name: LEATHER PRO-TECH

(Contd. of page 5)

Dangerous Goods Class	
ADG Class:	3 Flammable liquids.
Packing Group:	
ADG, IMDG, IATA	II
EMS Number:	F-E,S-D
Hazchem Code:	•2YE
Limited Quantities:	1L
Packagings & IBCs - Packing Instruction:	P001, IBC02
Portable Tanks & Bulk Containers - Instructions:	T4
Portable Tanks & Bulk Containers - Special Provisions:	TP1

15 Regulatory Information

Australian Inventory of Chemical Substances:

CAS: 67-63-0	Propan-2-ol
CAS: 1071-76-7	Zirconium tetrabutanolate

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:
Not Scheduled.

16 Other Information

Date of Preparation or Last Revision: 07.06.2019

Prepared by: MSDS.COM.AU Pty Ltd

www.msds.com.au

Abbreviations and acronyms:

ADG: Australian Dangerous Goods
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 LC₅₀: Lethal concentration, 50 percent
 LD₅₀: Lethal dose, 50 percent
 IARC: International Agency for Research on Cancer
 STEL: Short Term Exposure Limit
 TWA: Time Weighted Average
 NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)
 Flammable Liquids 2: Flammable liquids – Category 2
 Serious Eye Damage/Irritation 2A: Serious eye damage/eye irritation – Category 2A
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document "Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016"

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Always Dry makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.